

PS28-12 (12V 28Ah)


Valve Regulated Lead Acid batteries are designed with AGM (Absorbent Glass Mat) technology, high performance plates and electrolyte to gain extra power output for common power backup system applications widely used in the field of UPS and Emergency Lighting System.

Application

- Alarm System
- Cable Television
- Power tools
- Emergency Power System
- Security System
- Medical Equipment
- UPS
- Communication Equipment
- Control Equipment
- Toys

General Features

- Sealed and maintenance free operation
- Non-spillable construction design
- ABS containers and covers (UL94HB, UL94V-0) optional
- Safety valve installation for explosion proof
- High quality and high reliability
- Exceptional deep discharge recovery performance
- Low self discharge characteristic
- Flexibility design for multiple installation positions



CONSTRUCTION

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Rubber	Lead	Fiberglass	Sulfuric acid

TECHNOLOGY PARAMETER

Battery model	PS28 - 12			
Designed Floating Life	3~5 Years			
Capacity (25°C)	20hR(1.4A, 10.5V)	10hR(2.6A, 10.5V)	5hR(4.54A, 10.5V)	1hR(17.4A, 9.60V)
	28Ah	26Ah	22.7Ah	17.4Ah
Dimensions	Length	Width	Height	Total Height
	165±1mm	125±1mm	175±1mm	182±1mm
Approx. weight (±5%)	7.60 Kg			
Internal resistance	Full charged at 25°C: 10mOhms			
Self discharge	3% of capacity declined per month at 25°C (average)			
Capacity Affected by Temp.(20HR)	40 °C	25 °C	0 °C	-15 °C
	102%	100%	85%	65%
Charge Voltage (25°C)	Cycle use		Float use	
	14.5-14.9V(-30mV/°C), max. Current: 8.4A		13.6-13.8V(-20mV/°C)	

Constant current discharge ratings-amperes at 25°C

End Point Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60V	103	72.3	55.1	31.0	17.4	7.58	4.95	2.74	1.47
1.65V	98.1	69.1	52.4	29.8	17.0	7.34	4.81	2.69	1.44
1.70V	92.3	65.2	49.7	28.5	16.6	7.09	4.68	2.64	1.42
1.75V	86.5	61.3	47.0	27.0	15.9	6.79	4.54	2.60	1.40
1.80V	80.7	58.1	44.3	25.7	15.2	6.48	4.40	2.55	1.38

Constant power discharge ratings-watts at 25°C

End Point Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60V	191	134	102	57.9	32.7	14.3	9.41	5.23	2.82
1.65V	181	127	96.9	55.4	31.9	13.8	9.10	5.11	2.75
1.70V	169	119	91.4	52.7	30.9	13.3	8.79	4.98	2.70
1.75V	157	111.6	86.0	49.8	29.4	12.6	8.49	4.90	2.65
1.80V	145	104.6	80.2	46.8	27.7	11.9	8.14	4.75	2.57

