



LED POWER SUPPLY DATASHEET

SNP100-24VFD-1(PUSH Dimming)

·DESCRIPTION

Linear type LED drivers,high cost performance and meet SELV standrad.Widely used in all kinds of advertising light boxes and board,neon lights and other applications.Can also be applied in cabinet furniture and linear luminaire field.Compliance to ERP directive,lifetime 30,000hrs. Slim design save much space for installation.Dimmable design meet the requirements for dimming of all kinds of linear light.



·Input

Items	Conditions	Request	Note
Input voltage	Ta	AC180-264V	--
Input frequency		50/60Hz	--
Input current	25℃,rated input voltage, output with max. rated power	< 0.7A	--
Input power		< 110W	--
Efficiency		≥ 92%	--
Standby		<0.5W	average
Inrush current	25℃,rated input voltage	<75A	peak
PF	25℃,rated input voltage, output max. rated power	≥ 0.9	--

·Temperate and others

Item	Conditions	Request	Note
Operation temp.	--	-20-55℃	--
Relative humidity	--	45%-85%	--
Max. case temp.	--	80℃	--
Lifetime	Max.Ta,rated input voltage,output with max.rated power	30,000hr	--
Working noise	25℃,rated input voltage,output with rated power ,mute box background noise<35dB,pickup 10cm distance from products	yes	--

·Protection

Items	Conditions	Request	Note
Open circuit	Ta, rated input voltage, no load	--	--
Over load	Ta ,0.94-1.06 times of input voltage, twice over of rated power	yes	--
Short circuit	Ta ,0.94-1.06 times of input voltage	yes	--
Over temperature	Ta ,0.94-1.06 times of input voltage, temperature detected point more than 115 degree	yes	--
Over voltage	Ta ,0.94-1.06 times of input voltage,output voltage is 1.5 times of rated one	yes	--
Auto recovery	Over load, short circuit revocation	yes	--
Latch off	Over voltage, over heat re-start after cut off	yes	--

·Output

Items	Conditions	Request	Note
Startup time	25℃, rated input voltage,output with max. rated power	<0.5S	--
Output voltage and precisio	Ta , rated input voltage, output with rated power	24V±5%	--
Output current range	Ta ,rated input voltage	0-4.16A	100W
Output voltage wave	25℃, rated input voltage,output with max. rated power	600mV	Vp-p
Output overload	25℃,rated input voltage,output with twice over LED load	yes	--
Output current and precisio	Ta , rated input voltage, output with rated power	--	--
Rated output voltage range	Ta , rated input voltage,	--	--
Output current wave	25℃, rated input voltage,output with max. rated power	--	Ip-p
Dimming mode	PUSH	yes	--
Dimming range	1-100%	yes	--

·Mechanical, mounting

Items	Conditions
Case material and size	Plastic case
Mounting ways	Built in
Insulation type	--
IP grade	IP20
Input cables dimension	--
Output cables dimension	--
Output cables length	--

·Standard

Items	Conditions
Safety	IEC61347-1、IEC61347-2-13
Harmonic	EN61000-3-2 Class C
EMI	EN55015
EMS	EN61000-4-2、3、4、5、6 EN61547



SNAPPY

KNOW HOW. NO LIMITS.

Dimming Opeartion

PUSH Dimming


Function	Press time
No change	<0.05 sec.
Push switch	0.1-1 sec.
Turn the light down or up	1.5-10 sec.

Factory setting 100%

Each press action changes the dimming direction



Dimensions(mm)



Wiring Diagram

